

IN THE CLAIMS:

1. (currently amended) In combination with a plurality of trays for holding pre-cooked food having been previously cooked in a cooking appliance, each tray having a bottom wall and side and end walls extending up from the bottom wall to an upper rim  
5 defining an open top of the tray, a food holding oven for holding pre-cooked food at a selected food holding temperature, said food holding oven comprising:

a cabinet having an interior;

partitions in the cabinet dividing said interior into a  
10 plurality of separate, thermally isolated holding compartments each adapted for removably receiving [[a]] one tray of said plurality of trays per compartment;

a plurality of heat sources in said compartments above said trays adapted for activation to emit radiant heat to the food in  
15 the trays to warm the food; and

a control mechanism for controlling operation of the heat sources independent of one another whereby the food holding temperature in each compartment may be independently controlled.

2. (original) A combination as set forth in claim 1 wherein said control mechanism comprises a timer control for setting a duration of holding time for each compartment independent of the other compartments, said duration of holding time comprising at  
5 least a duration of heated holding time during which a respective heat source is activated.

3. (original) A combination as set forth in claim 2 wherein said duration of holding time comprises the sum of said duration of heated holding time and a duration of non-heated holding time

during which a respective heat source is not activated.

4. (original) A combination as set forth in claim 1 wherein said control mechanism is operable to activate and deactivate at least one of said heat sources during successive duty cycles thereby to maintain the food in a respective compartment at a selected holding temperature for a duration of heated holding time, each duty cycle comprising a heating interval followed by a non-heating interval.

5. (original) A combination as set forth in claim 4 wherein said control mechanism comprises a duty-cycle control for controlling the length of the heating interval of a duty cycle.

6. (original) A combination as set forth in claim 4 wherein said control mechanism comprises a temperature control for selecting the holding temperature in each compartment.

7. (original) A combination as set forth in claim 6 wherein said control mechanism is operable to deactivate the heat source in at least one compartment while the temperature of the food in said compartment cools down to said selected holding temperature during a duration of non-heated holding time, and for then activating and deactivating the heat source in said at least one compartment during said successive duty cycles thereby to maintain the food in the compartment at said selected holding temperature for said duration of heated holding time.

8. (original) A combination as set forth in claim 7 further comprising a forced air mechanism for delivering cooling air into

the compartments, said control mechanism being operable to  
activate the forced air mechanism during said duration of non-  
5 heating holding time.

9. (original) A combination as set forth in claim 7 wherein  
said control mechanism comprises a timer control for setting a  
duration of holding time for each compartment independent of the  
other compartments, said duration of holding time comprising at  
5 least a duration of heated holding time during which a respective  
heat source is activated.

10. (original) A combination as set forth in claim 9  
wherein said timer control is operable for setting a duration of  
holding time comprising the sum of said duration of non-heated  
holding time and said duration of said heated holding time.

11. (original) A combination as set forth in claim 6  
wherein said control mechanism is operable to activate the heat  
source in at least one compartment to raise the temperature in  
the compartment to said selected holding temperature during a  
5 duration of rethermalizing holding time, and for then activating  
and de-activating the heat source in said at least one  
compartment during said successive duty cycles thereby to  
maintain the food in the compartment at said selected holding  
temperature for said duration of heated holding time.

12. (original) A combination as set forth in claim 11  
wherein said control mechanism comprises a timer control for  
setting a duration of holding time comprising at least said  
duration of holding time comprising at least a duration of heated

5 holding time during which a respective heat source is activated.

13. (original) A combination as set forth in claim 12 wherein said timer control is operable for setting a duration of holding time comprising the sum of said duration of rethermalizing holding time and said duration of said heated  
5 holding time.

14. (original) A combination as set forth in claim 1 further comprising a forced air mechanism under the control of said control mechanism for delivering forced air into the compartments.

15. (original) A combination as set forth in claim 14 wherein said forced air mechanism comprises lower air ducting for conveying forced air into the compartments at locations below the trays in the compartments.

16. (original) A combination as set forth in claim 15 wherein said forced air mechanism comprises upper air ducting for conveying forced air out of the compartments at locations above the trays in the compartments.

17. (original) A combination as set forth in claim 16 wherein said forced air mechanism further comprises a fan system for moving air through said upper and lower air ducting.

18. (original) A combination as set forth in claim 17 wherein said fan system is operable in a first mode to circulate air in one direction along a flow path comprising said lower air ducting, said compartments and said upper air ducting, and in a

5 second mode to circulate air in an opposite direction along said flow path.

19. (original) A combination as set forth in claim 18 further comprising heat sources positioned in at least one of said upper and lower air ducting for heating air flowing along said flow path.

20. (original) A combination as set forth in claim 19 wherein said control mechanism further comprises temperature sensors in the compartments for sensing the temperatures in the compartments, said control mechanism being operable in response  
5 to signals from said temperature sensors to control the operation of said fan system.

21. (original) A combination as set forth in claim 14 wherein said forced air is convective heating air.

22. (original) A combination as set forth in claim 21 wherein said trays have holes therein for allowing forced air entering the compartments to flow through the holes and thereby remove moisture from the food therein.

23. (original) A combination as set forth in claim 1 wherein said heat source is selected from a group comprising a quartz infrared heat source, a halogen infrared heat source, a ceramic infrared heat source, and a resistance heating element  
5 embedded in magnesium oxide.

24. (previously presented) A combination as set forth in

claim 1 wherein at least some of said trays have one or more vent hole openings for venting moisture from the tray.

25. (original) A combination as set forth in claim 24 wherein different trays have different hole patterns.

26. (original) A combination as set forth in claim 24 wherein different trays have different hole sizes.

27. (original) A combination as set forth in claim 1 further comprising a panel positioned between a heat source and its respective compartment.

28. (original) A combination as set forth in claim 1 wherein said partitions prevent the transfer of food flavors between the compartments.

29. (original) A combination as set forth in claim 1 wherein said heat source comprises one or more electric heating elements located over said trays.

30. (original) A combination as set forth in claim 1 wherein the power delivered by each heat source ranges from 40-600 watts.

31. (original) A combination as set forth in claim 1 further comprising vertically spaced shoulders in each compartment at opposite sides of the compartment for supporting a tray at different elevations in the compartment.

32. (original) A combination as set forth in claim 1 wherein said compartments have different widths.

33. (original) A combination as set forth in claim 1 wherein said heat sources comprise electric resistance heating elements.

34. (original) A method of controlling the operation of a food holding oven, said oven comprising a cabinet, a plurality of separate, thermally isolated holding compartments in the cabinet, each compartment being adapted for removably receiving a tray for  
5 containing pre-cooked food having been previously cooked in a cooking appliance, and a heat source above a respective tray for emitting radiant heat to the food in the tray to warm the food, said method comprising activating and deactivating each heat source during successive duty cycles thereby to maintain the food  
10 in a respective compartment at a selected holding temperature for a duration of heated holding time, each duty cycle comprising a heating interval followed by a non-heating interval.

35. (original) A method as set forth in claim 34 further comprising varying the length of the heating interval of a duty cycle.

36. (original) A method as set forth in claim 34 further comprising maintaining at least two compartments at different selected holding temperatures.

37. (original) A method as set forth in claim 34 further comprising placing a tray containing food at a temperature above

5 said selected holding temperature into a respective compartment,  
deactivating the heat source in the compartment while the food in  
the compartment cools down during a duration of non-heated  
holding time, and then activating and deactivating the heat  
source in said at least one compartment during said successive  
duty cycles thereby to maintain the food in the compartment at  
said selected holding temperature for said duration of heated  
10 holding time.

38. (original) A method as set forth in claim 37 further  
comprising delivering cooling air into the compartments during  
said duration of non-heating holding time.

39. (original) A method as set forth in claim 37 further  
comprising placing a tray containing food at a temperature below  
said selected holding temperature into a respective compartment,  
activating the heat source in the compartment to raise the  
5 temperature in the compartment to said selected holding  
temperature during a duration of rethermalizing holding time, and  
then activating and deactivating the heat source in said at least  
one compartment during said successive duty cycles thereby to  
maintain the food in the compartment at said selected holding  
10 temperature for said duration of heated holding time.

40. (original) A method as set forth in claim 34 further  
comprising setting a duration of holding time for each  
compartment independent of the other compartments, said duration  
of holding time comprising at least a duration of heated holding  
5 time during which a respective heat source is activated.



41. (original) A method as set forth in claim 40 wherein said duration of holding time comprises the sum of said duration of heated holding time and a duration of non-heated holding time during which a respective heat source is not activated.

42. (original) A method as set forth in claim 34 further comprising conveying convective heating air into the compartments.

43. (original) A method as set forth in claim 42 further comprising conveying said convective heating air into the compartments at locations below the trays for flow in a generally upward direction toward said trays.

44. (original) A method as set forth in claim 42 further comprising conveying said convective heating air into the compartments at locations above the trays for flow in a generally downward direction toward said trays.

45. (original) A method as set forth in claim 42 further comprising circulating heating air through the compartments in one direction and then reversing the direction of air flow to circulate heating air through the compartments in a different  
5 direction.

46. (original) A method as set forth in claim 34 further comprising varying the vertical position of at least one tray in a respective compartment.

47. (currently amended) A method of controlling the

operation of a food holding oven, said oven comprising a cabinet,  
a plurality of separate, thermally isolated holding compartments  
in the cabinet, a plurality of trays for containing pre-cooked  
5 food having been previously cooked in a cooking appliance, each  
compartment being adapted for removably receiving [[a]] one tray  
per compartment ~~for containing pre-cooked food having been~~  
~~previously cooked in a cooking appliance~~, and heat sources above  
respective trays adapted for activation to emit radiant heat to  
10 the food in the trays to warm the food, said method comprising:  
    setting a selected holding temperature for each compartment;  
    setting a duration of holding time for each compartment,  
said duration of holding time comprising a duration of heated  
holding time; and  
15      activating each heat source during a respective duration of  
heated holding time thereby to maintain the food in a respective  
compartment at said selected holding temperature.

48. (original) A method as set forth in claim 47 wherein  
said duration of holding time comprises the sum of said duration  
of heated holding time and a duration of non-heated holding time  
during which a respective heat source is not activated.

49. (original) A method as set forth in claim 47 further  
comprising placing a tray containing food at a temperature above  
said selected holding temperature into a respective compartment,  
deactivating the heat source in the compartment while the  
5 temperature in the compartment cools down to said selected  
holding temperature during a duration of non-heated holding time,  
and then activating and deactivating the heat source in said at  
least one compartment during successive duty cycles thereby to

10 maintain the food in the compartment at said selected holding  
temperature for said duration of heated holding time.

50. (original) A method as set forth in claim 49 further  
comprising delivering cooling air into the compartments during  
said duration of non-heating holding time.

51. (original) A method as set forth in claim 50 further  
comprising placing a tray containing food at a temperature below  
said selected holding temperature into a respective compartment,  
activating the heat source in the compartment to raise the  
5 temperature in the compartment to said selected holding  
temperature during a duration of rethermalizing holding time, and  
then activating and deactivating the heat source in said at least  
one compartment during said successive duty cycles thereby to  
maintain the food in the compartment at said selected holding  
10 temperature for said duration of heated holding time.

52. (original) In combination with a plurality of trays for  
holding warm food, each tray having a bottom wall and side and  
end walls extending up from the bottom wall to an upper rim  
defining an open top of the tray, an oven for transferring heat  
5 to food in the trays, said oven comprising:

a cabinet having an interior for removably receiving said  
plurality of trays;

10 a plurality of covers covering the open tops of the trays,  
each cover having a metallic portion overlying the top of a  
respective tray;

a source for heating the metallic portion of each cover  
whereby the metallic portion is adapted to emit radiant heat to

the food in the respective tray to warm the food in the tray; and  
one or more openings in at least some of the covers for  
15 venting moisture from each tray having such a cover.

53. (original) A combination as set forth in claim 52  
wherein one or more of said covers are in sealing contact with  
the rims of respective trays.

54. (original) A combination as set forth in claim 52  
wherein one or more of said covers are spaced above the rims of  
respective trays by a distance no greater than one inch.

55. (original) A combination as set forth in claim 52  
wherein one or more of said covers are spaced above the rims of  
respective trays by a distance no greater than about 0.40 in.

56. (original) A combination as set forth in claim 52  
wherein said source comprises one or more electric heating  
elements located over said covers.

57. (original) A combination as set forth in claim 56  
wherein each heating element is enclosed in a housing affixed to  
an interior surface of the cabinet.

58. (original) A combination as set forth in claim 52  
wherein said source is spaced above each cover a distance less  
than 2.0 inches.

59. (original) A combination as set forth in claim 52  
wherein said source is spaced above each cover a distance less

than 1.0 inches.

60. (original) A combination as set forth in claim 52 further comprising a plurality of tray-receiving members in said cabinet, each being sized and configured for holding a single tray.

61. (original) A combination as set forth in claim 60 wherein said tray-receiving members are heat sinks each having a bottom wall and side walls extending up from the bottom wall for receiving a tray therebetween.

62. (original) A combination as set forth in claim 61 wherein the side walls of each heat sink have generally horizontal shoulders for supporting one of said covers over the tray.

63. (original) A combination as set forth in claim 62 wherein each cover comprises a generally horizontal metal cross wall and legs extending down from the cross wall for bearing on the shoulders of a respective heat sink, the spacing between the cross wall of the cover and the bottom wall of the heat sink being not substantially greater than the height of the tray received in the heat sink.

64. (original) A combination as set forth in claim 52 wherein the combined areas of said one or more openings in a cover is less than 25% of the area of the open top of the tray it is covering.

65. (original) A combination as set forth in claim 52 wherein the combined areas of said one or more openings in a cover is less than 5% of the area of the open top of the tray it is covering.

66. (original) A combination as set forth in claim 52 wherein the combined areas of said one or more openings in a cover is less than 1% of the area of the open top of the tray it is covering.

67. (original) A combination as set forth in claim 52 wherein the heat source is operable to heat each cover to a temperature ranging from 200-500° F.

68. (original) A combination as set forth in claim 52 wherein the power delivered by said heat source to each cover ranges from 100-500 watts.

69. (original) A cover for covering a tray received in an oven having a heat source therein, each tray having a bottom wall and side and end walls extending up from the bottom wall to an upper rim defining an open top of the tray, said cover  
5 comprising:

a metallic wall adapted to overlies the open top of tray for receiving heat from said heat source and for emitting radiant heat to the food in the tray to warm it; and

10 one or more openings in the cover for venting moisture from the tray.

70. (original) A cover as set forth in claim 69 wherein

said metallic wall extends generally horizontally over the tray, said cover further comprising legs extending down from the cross wall for supporting the cover in the oven over the tray.

71. (original) A cover as set forth in claim 69 wherein the combined areas of said one or more openings is less than 25% of the area of the open top of the tray.

72. (original) A cover as set forth in claim 71 wherein the combined areas of said one or more openings is less than 5% of the area of the open top of the tray.

73. (original) A cover as set forth in claim 72 wherein the combined areas of said one or more openings is less than 1% of the area of the open top of the tray.

74. (previously presented) A combination as set forth in claim 1 wherein said control mechanism is operable to control operation of each heat source to deliver heat to the food in a respective tray to warm the food to a selected holding  
5 temperature, and then to vary the amount of heat delivered to the food to hold the food at said selected holding temperature.

75. (previously presented) A combination as set forth in claim 74 wherein said control mechanism comprises an operator input device for selecting a type of food to be placed in said compartment, and wherein said control mechanism is programmed for  
5 operating the heat source according to a predetermined protocol depending on the type of food selected.

76. (currently amended) A combination as set forth in claim 1 wherein said control mechanism is programmed to operate said heat source according to a predetermined protocol to vary said heat delivered to said ~~heat source~~ food depending on the type of food placed in the compartment.

77. (previously presented) A combination as set forth in claim 1 wherein said control mechanism comprises an operator input device for selecting a type of food placed in a respective compartment, and wherein said control mechanism is programmed to operate a respective heat source to heat the food in said respective compartment to a pre-programmed selected holding temperature, and then to hold the food at said pre-programmed selected holding temperature.

78. (previously presented) A combination as set forth in claim 77 wherein said control mechanism is responsive to said operator input device to operate the heat source to hold the food at said pre-programmed selected holding temperature for a pre-programmed holding duration.

79. (previously presented) A method as set forth in claim 34 wherein the food is placed in the compartment at a temperature less than ambient temperature, and wherein said method further comprising activating the heat source to deliver heat to the food until the food reaches said selected holding temperature, and then varying the amount of heat delivered to the food to maintain the food at said selected holding temperature.



80. (previously presented) A method as set forth in claim 79 wherein said method further comprising programming said oven to heat the food in each compartment to a selected holding temperature which varies depending to the type of  
5 food placed in the compartment.

81. (previously presented) A method as set forth in claim 47 wherein the food is placed in the compartment at a temperature less than ambient temperature, and wherein said  
5 method further comprises activating the heat source to deliver heat to the food until the food reaches said selected holding temperature, and then varying the amount of heat delivered to the food to maintain the food at said selected holding temperature.

82. (previously presented) A method as set forth in claim 81 wherein said method further comprising programming said oven to heat the food in each compartment to a selected  
5 holding temperature which varies depending to the type of food placed in the compartment.

83. (cancelled)

84. (previously presented) In combination with a plurality of trays for holding warm food, each tray having a bottom wall and side and end walls extending up from the  
5 bottom wall to an upper rim defining an open top of the tray, at least some of said trays having at least one vent hole opening for venting moisture from the tray, an oven for transferring heat to food in the trays, said oven comprising:  
10 a cabinet having an interior;  
partitions in the cabinet dividing said interior into a

plurality of separate, thermally isolated holding compartments each adapted for removably receiving a tray of said plurality of trays;

15 a plurality of heat sources in said compartments above said trays adapted for activation to emit radiant heat to the food in the trays to warm the food; and

a control mechanism for controlling operation of the heat sources independent of one another whereby the  
20 temperature in each compartment may be independently controlled.

85. (previously presented) A method of controlling the operation of an oven, said oven comprising a cabinet, a plurality of separate, thermally isolated holding  
5 compartments in the cabinet, each compartment being adapted for removably receiving a tray for containing food, and a heat source above a respective tray for emitting radiant heat to the food in the tray to warm the food, said method comprising activating and deactivating each heat source  
10 during successive duty cycles, each duty cycle comprising a heating interval followed by a non-heating interval, and varying the length of time for the heating interval of the duty cycle to maintain the food in a respective compartment at a selected holding temperature for a duration of heated  
15 holding time.

86. (previously presented) A method of controlling the operation of an oven, said oven comprising a cabinet, a plurality of separate, thermally isolated holding  
5 compartments in the cabinet, each compartment being adapted for removably receiving a tray for containing food, and heat sources above respective trays adapted for activation to emit radiant heat to the food in the trays to warm the food,

said method comprising:

- 10        setting a selected holding temperature for each  
compartment;  
         setting a duration of holding time for each  
compartment, said duration of holding time comprising a  
duration of heated holding time;
- 15        activating each heat source during a respective  
duration of heated holding time thereby to maintain the food  
in a respective compartment at said selected holding  
temperature;
- placing a tray containing food at a temperature above  
20        said selected holding temperature into a respective  
compartment;
- deactivating the heat source in the compartment while  
the temperature in the compartment cools down to said  
selected holding temperature during a duration of non-heated  
25        holding time; and
- activating and deactivating the heat source in said at  
least one compartment during successive duty cycles thereby  
to maintain the food in the compartment at said selected  
holding temperature for said duration of heated holding  
30        time.

87. (currently amended). A food holding oven for  
holding pre-cooked food at a selected food holding  
temperature, said food holding oven comprising:

- 5        a cabinet having a front, a rear, and an interior  
space;
- a plurality of separate, thermally isolated holding  
compartments in the interior space of the cabinet for  
receiving trays for holding the pre-cooked food, each  
10        compartment being adapted for receiving one tray per  
compartment;

each compartment having an open front end at the front of the cabinet for placement of a respective tray in the compartment and removal of said tray from the compartment;

15       the cabinet having a first row of compartments and a second row of compartments, the first row being arranged above the second row;

20       a plurality of heat sources in said compartments above said trays adapted for activation to emit radiant heat to the food in the trays to warm the food; and

      a control mechanism for controlling operation of the heat sources independent of one another whereby the food holding temperature in each compartment may be independently controlled.

88. (previously presented) A food holding oven as set forth in claim 87 wherein each compartment has an open back end at the rear of the cabinet for placement of a respective  
5   tray in the compartment and removal of said tray from the compartment.

89. (previously presented) A food holding oven as set forth in claim 87 wherein the front ends of said compartments are doorless and remain open during a heating operation.

90. (previously presented) A food holding oven as set forth in claim 87 wherein said control mechanism is operable to control operation of each heat source to deliver heat to the food in a respective tray to warm the food to a selected  
5   holding temperature, and then to vary the amount of heat delivered to the food to hold the food at said selected holding temperature.

91. (currently amended) A food holding oven as set forth in claim 87 wherein said control mechanism is programmed to operate said heat source according to a predetermined protocol to vary said heat delivered to said  
5 ~~heat source~~ food depending on the type of food placed in the compartment.

92. (previously presented) A food holding oven as set forth in claim 87 wherein said control mechanism comprises an operator input device for selecting a type of food placed in a respective compartment, and wherein said control  
5 mechanism is programmed to operate a respective heat source to heat the food in said respective compartment to a pre-programmed selected holding temperature and to hold the food at said pre-programmed selected holding temperature.

93. (previously presented) The food holding oven as set forth in claim 87 wherein said cabinet has a top, bottom and opposite sides, the cabinet being sized such that the distance between the opposite sides is greater than the  
5 distance between the top and bottom of the cabinet.

94. (previously presented) The food holding oven as set forth in claim 93 wherein said control mechanism comprises an operator input device below the top of the cabinet and adjacent a side of the cabinet.

95. (new) A food holding oven for holding pre-cooked food at a selected food holding temperature, said food holding oven comprising:

a cabinet having a front, a rear, and an interior  
5 space;

a plurality of separate, thermally isolated holding

compartments in the interior space of the cabinet for receiving trays for holding the pre-cooked food;

10 a plurality of heat sources in said compartments above said trays adapted for activation to emit radiant heat to the food in the trays to warm the food; and

15 a control mechanism for controlling operation of the heat sources independent of one another whereby the food holding temperature in each compartment may be independently controlled, the control mechanism being operable to activate and deactivate at least one of said heat sources during duty cycles thereby to maintain the food in a respective  
20 compartment at a selected holding temperature for a duration of heated holding time, each duty cycle comprising a heating interval during which the heat source is activated followed by a non-heating interval during which the heat source is not activated.

96. (new) A food holding oven as set forth in claim 95 wherein said control mechanism comprises a control for setting said heating interval and said non-heating interval for each duty cycle.

97. (new) A food holding oven as set forth in claim 95 wherein said control mechanism comprises an operator input device for selecting a type of food to be placed in said compartment, and wherein said control mechanism operates said  
5 heat sources in successive duty cycles according to a predetermined protocol depending on the type of food selected.

98. (new) A food holding oven as set forth in claim 97 wherein said control mechanism sets the heating interval and non-heating interval based on the type of food selected.

99. (new) A food holding oven as set forth in claim 97 wherein each duty cycle has the same heating interval and each duty cycle has the same non-heating interval for the type of food selected.

100. (new) A food holding oven as set forth in claim 95 wherein each duty cycle comprises a time-base defined by the total time for the heating interval and the non-heating interval, said control mechanism comprising an operator input  
5 device for selecting said time-base.

101. (new) A food holding oven as set forth in claim 95 wherein each duty cycle comprises a time-base defined by the total time for the heating interval and the non-heating interval, said time-base being preset according to a type of  
5 food placed in the holding oven.

102. (new) A combination as set forth in claim 1 wherein said control mechanism is operable to activate and deactivate at least one of said heat sources during duty cycles thereby to maintain the food in a respective compartment at a selected  
5 holding temperature for a duration of heated holding time, each duty cycle comprising a heating interval during which the heat source is activated followed by a non-heating interval during which the heat source is not activated.

103. (new) A combination set forth in claim 102 wherein said control mechanism comprises an operator input device for selecting a type of food to be placed in said compartment, and wherein said control mechanism operates said heat sources in

5 successive duty cycles according to a predetermined protocol depending on the type of food selected.

104. (new) A combination set forth in claim 103 wherein said control mechanism operates said heat sources according to a predetermined protocol to vary said heating interval and said non-heating interval heat based on the type of food  
5 placed in a respective compartment.

105. (new) A combination as set forth in claim 102 wherein each duty cycle comprises a time-base defined by the total time for the heating interval and the non-heating interval, said control mechanism comprising an operator input  
5 device for selecting said time-base.

106. (new) A combination as set forth in claim 102 wherein each duty cycle comprises a time-base defined by the total time for the heating interval and the non-heating interval, said time-based being preset according to a type of  
5 food placed in the holding oven.

107. (new) A method as set forth in claim 34 wherein each duty cycle has the same heating interval and the same non-heating interval.

108. (new) A method as set forth in claim 34 further comprising programming said oven to operate said heat source according to a predetermined protocol to vary said heating interval and said non-heating interval based on the type of  
5 food placed in a respective compartment.



109. (new) A method as set forth in claim 34 wherein each duty cycle comprises a time-base defined by the total time for the heating interval and the non-heating interval, said method further comprises selecting said time-base.

110. (new) A method as set forth in claim 34 wherein each duty cycle comprises a time-base defined by the total time for the heating interval and the non-heating interval, said method further comprising programming said oven to  
5 operate according to a preset time-base according to a type of food placed in the oven.